

R135

SKID LOADERS



GEHL®

Hoedanigheid		Metrisch	Imperiaal
Rated Operating Capacity		612 kg	1349 lb
Rated Operating Capacity with Optional Counterweight		680 kg	1499 lb
Leeg gewicht		2383.62 kg	5255 lb
Gewicht en afmetingen			
Overall Operating Height - Fully Raised	h27	3670.30 mm	144 in
Hoogte tot scharnierpen - volledig verhoogd	h28	2790 mm	110 in
Overall Height to Top of ROPS	h17	1930 mm	76 in
Storhoek op volledige hoogte	a5	40 °	40 °
Dump height	h29	2120 mm	83 in
Overall length with bucket	l16	3073.40 mm	121 in
Dump reach - Full height	r6	591 mm	23 in
Terugrollen op de grond	a13	28 °	28 °
Seat to ground height	h30	871.22 mm	34 in
Wielbasis (y)	y	950 mm	37 in
Overall width less bucket	b1	1364 mm	54 in
Bakbreedte	e1	1372 mm	54 in
Bodemvrijheid machine	m4	201 mm	8 in
Overall length - Less Bucket	l2	2359.66 mm	93 in
Clearance Radius - Front with Bucket	b18	1842 mm	73 in
Vrije ruimte (straal) - Vooraan zonder bak	b19	1120 mm	44 in
Clearance Circle - Rear	wa1	1372 mm	54 in
Prestatie			
Rijsnelheid (onbelast)		12.90 km/h	8 mi/h
Banden			
Standard tyres		10.00x16.5 HD	10.00x16.5 HD
Motor			
Merk		Yanmar	Yanmar
Motormodel		4TNV88C	4TNV88C
Motornorm		Stage V / Tier 4	Stage V / Tier 4
Gross Power (kW)		34.30 kW	34 kW
Net Power (kW)		33.20 kW	33 kW
Max. koppel / Motorkoppel		146.20 Nm / 1820 rpm	108 ft/lbs / 1820 rpm
Batterij		12 V	12 V
Starter (kW)		2.30 kW	2 kW
Hydraulisch			
Hulphydrauliek		63.60 l/min	17 US gpm
Tankinhoud			
Inhoud brandstoftank		59.40 l	16 US gal
Cilinderinhoud		2.19 l	0.58 US gal
Geluid en trillingen			
Lawaai in de omgeving (LwA)		101 dB	101 dB
Whole-Body Vibration (ISO 2631-1)		0.81 m/s ²	0.81 m/s ²
Trillingen op het geheel handen/armen		< 1.77 m/s ²	< 1.77 m/s ²



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend